

Geocel® ECOCHEM STAYPUTT BLOCK PAVING NARROW JOINTING COMPOUND For narrow joints 2mm – 5mm

STAYPUTT BLOCK PAVING Narrow Jointing Compound is suitable for concrete, clay and blocks or any hard landscaping with narrow joints laid on a sharp sand screed. It is ideal for both new and refurbishment, commercial and residential applications.

STAYPUTT BLOCK PAVING Narrow Jointing Compound is a greener product as it is cement and solvent free. Cement is hazardous to health and can cause allergic reactions. Products containing cement and solvents can stain surfaces. **STAYPUTT BLOCK PAVING** Jointing Compound uses polymer binders as an alternative to cement and solvents, and therefore does not stain. **STAYPUTT BLOCK PAVING** Narrow Jointing Compound also reduces waste as it is not vacuum packed and it can be reused.

STAYPUTT BLOCK PAVING:

- Totally unique patented technology
- Easy to apply as kiln dried jointing sand but with added benefits
- Reusable – not vacuum packed so there's NO WASTE
- Ready to use – just SWEEP, WET & GO
- Non staining
- Tough & long lasting - SUPERIOR ADHESION
- Inhibits moss, weeds, algae growth & removal by insects
- Can be pressure washed*
- Water permeable – allows water to escape



TECHNICAL DATA

Form	Sand
Storage Life	12 Months
Colours	Natural & Grey

Specification writers: These values are not intended for use in preparing specifications. Please contact your local **Geocel® Sales Representative** prior to writing specifications on this product.

SURFACE PREPARATION

Ensure surfaces are dry before application.

APPLICATION

ON NEW INSTALLATIONS:

Give the tub a good shake before using to ensure that the polymers are mixed. Pour **STAYPUTT BLOCK PAVING** Narrow Jointing Compound onto surface.

Brush into joints with a normal sweeping motion until all joints are filled. Top up joints where necessary and brush off excess.

Excess product can be reused. IT MUST BE KEPT DRY.

Wet thoroughly using a fine hose spray. Any excess residue that has adhered to paving surface should be rewetted immediately and scrubbed lightly with a semi stiff bristle broom, then washed off with a fine hose spray attachment. Do not wet the area excessively.

Allow 48 hours to cure. Drying time is dependent on ambient temperature and weather conditions.

Walk on or drive on immediately.

ON REFURBISHED BLOCKS:

Pressure wash all joints thoroughly to remove debris and old sand down to a minimum depth of at least 25mm.

Allow to dry thoroughly.

Then follow steps as for new installation.

COVERAGE

Coverage per 15kg tub:

Slab Size	Depth	Joint Width	Coverage
200 x 95	50mm	2mm	6.0 m ²
200 x 95	60mm	2mm	5.0 m ²
200 x 95	80mm	2mm	3.75 m ²

LIMITATIONS

- Do not use on joints greater than 6mm. **STAYPUTT PAVING** is recommended for joints 6mm – 25mm.
- Do not apply when rain is imminent or temperatures are below 5°C.
- Cannot be applied to areas that are prone to water logging or excessive dampness.
- *Joints should not be cleaned using a pressure washer until thoroughly cured. Light pressure washing is recommended. The distance between the joint and pressure washer nozzle must be at least 10cm and not held in the same position.
- Not recommended for paving finishes with highly fissured surfaces, due to the difficulty removing excess product.

STORAGE

Best stored under cover and in dry conditions. Lid must be resealed after use.

PACKAGING

STAYPUTT BLOCK PAVING is available in 15kg resealable tubs.

HEALTH AND SAFETY

Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact **Geocel® Technical Service**.

*STAYPUTT is a registered trademark of STAYPUTT UK LTD
Worldwide Patents: Patent No: GB2398791, GB2381529*

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damages

Geocel®

Geocel Limited

Western Wood Way, Langage Science Park, Plympton, Plymouth, Devon, PL7 5BG

Tel: 01752 334350 Fax: 01752 202065 Email: info@geocel.co.uk

www.geocel.co.uk